

The reliable, multifunctional and maintenance-free unit for dependable level monitoring of bulk goods – versatile, small modular structure, also for use in Hazardous Locations (dust)

# Rotonivo® 3000



- suitable for nearly all bulk goods
- **■** insensitive to dust, electrical charges, adhesion, temperature and pressure

design with 1" protection tube or ex-

tension rope, vertical installation

■ simple and reliable measuring principle, easy, fast installation

RN 3002

**Full detector** 

Use: The Rotonivo® 3000 can be used as a full, demand or empty detector in bulk good silos depending on needs. It is one of our most versatile units and is suitable for a wide variety of materials, e.g. grains, milk powder, feed, detergent, chalk, cement, plastic granulate, wood chips and much more.

# RN 3001

### **Full, demand, empty detector** Standard design, vertical, horizontal and oblique installation



# RN 3004


Full, demand, empty detector design with 1" protection tube, vertical, horizontal and oblique installation



# RN 3003

Full, demand, empty detector design with protection tube and angular gear, horizontal installation





Technical Data	
Housing	Aluminium IP 66
Certificates	ATEX II 1/2 D
Process- temperature	-25°C upto +600°C
Pressure	max. +10bar
Sensitivity	min. 20g /I – adjustable in 3 steps
Mains voltage	110-120V or 220-240V AC 50-60Hz, 24V or 48V AC 50-60Hz, 24V DC
Process- connection	G1, G1½ and G1¼ inches, NPT1½ and NPT 1¼ inches, M30x1,5, M32x1,5
Bearing	Ball bearing with shaft sealing